

Features

Snap-in type Plug polishing holder

> Available in both IPC type works with existing SFP-550 series polishing machines and DPC (Fixed) type works with new SFP-560A series

For SFP-550 series: PH55-SN-24 SN/PC 24-plugs

PH55-SN8A-24 SN/APC 24-plugs

For SFP-560A series: PH55-SN-24FX SN/PC 24-plugs

PH55-SN8A-24FX SN/APC 24-plugs

> Holders for CS & SN ferrule polishing (IP16) and SN-BTW1 are also available. Please contact us.

■ Typical Polishing Process (case for SN/PC IPC type)

STEP	PAD	FILM	LIQUID	TIME (SEC)	PRESSURE
1st.	PR5X-500-80	GA5D	D.I Water	20	After 20 revs
2nd.	PR5X-500-80	EDH5D-3U	D.I Water	40	After start
3rd.	PR5X-500-80	EDJ5D-1U	D.I Water	40	After start
Final	PR5X-500-80	XF5D	D.I Water	40	After start

中国大陆代理商

深圳市谱兆通讯设备有限公司

Tel:+86-755-8665-5448;+86-755-8665-5579; Email:info@pztest.com Website:www.pztest.com

Seikoh Giken reserves the right to improve, enhance and modify features and specifications of Seikoh Giken products without prior notifications

