

OmniMarker II

OmniMarker-ID

Electronic markers are a smart, cost-effective way to protect underground assets, ensuring contractors can quickly and accurately locate utilities, fittings, and splices while avoiding costly damage and downtime. **OmniMarker II** continues Tempo Communications' legacy of reliability, offering exceptional range in a compact, environmentally friendly, maintenance-free design that can be located with any compatible marker locator.

For projects that demand more than just identification, **OmniMarker-ID** takes utility marking to the next level. In addition to a unique serial number, OmniMarker-ID allows critical information to be stored directly on the marker, instantly retrievable with a locator, and seamlessly integrated into a company's GIS system. This added intelligence makes OmniMarker-ID ideal for safeguarding critical infrastructure, working in crowded utility corridors, and providing richer data for long-term asset management.

Using a combination of the passive OmniMarker II for standard applications and OmniMarker-ID for high-priority sites delivers a powerful, flexible solution that saves time, reduces risk, and improves operational efficiency. Mark It. Map It. Manage It.

USE THE OMNIMARKER TO MARK AND FIND:

- Buried splices
- Buried service drops
- Pipe ends
- Conduit stubs
- Road crossings
- Cable paths
- Fiber optic facilities
- Manholes under pavement or grade changes
- Snow-covered installations
- Military caches
- Survey points
- Septic installations
- Repair points
- Non-metallic lines



OmniMarker II

S/N: 0848854435
Type: Blue/Water
 Object ID: 50
 Facility Number: 5453468
 Facility Type: Water Main
 Material: Polyvinyl Chloride
 Pipe Type: Distribution



OmniMarker-ID

OmniMarkers II / OmniMarker-ID patented self-leveling large diameter coil structure ensures precise location.



OMNIMARKER SPECIFICATIONS:

| | |
|---------------------------|---|
| SIZE | 4.0 inch diameter (100 mm) Min. |
| WEIGHT: | 0.3 lb (0.15 kg) |
| SHIPPING WEIGHT: | 11.3 lbs per carton of 30 (5.2 kg per carton of 30) |
| PASSIVE DETECTION RANGE: | 5 feet typical (1.5 meters) |
| OMNIMARKER ID READ RANGE: | 5 feet typical (1.5 meters) |
| FIELD TYPE: | Vertical dipole |
| EXTERNAL MATERIAL: | High-density polyethylene |

ORDERING INFORMATION:

| APPLICATION | COLOR | FREQUENCY | OMNIMARKER II | OMNIMARKER ID |
|-------------------|--|-----------|---------------|---------------|
| Non-Potable Water | Purple  | 66.4 kHz | OM-01 | OM01-ID |
| Cable TV | Orange Black  | 77.0 kHz | OM-02 | OM02-ID |
| Gas | Yellow  | 83.0 kHz | OM-03 | OM03-ID |
| Fiber Optic | Yellow Black  | 92.0 kHz | OM-04 | OM04-ID |
| Telephone | Orange  | 101.4 kHz | OM-05 | OM05-ID |
| Sanitary | Green  | 121.6 kHz | OM-06 | OM06-ID |
| Europower | Blue Red  | 134.0 kHz | OM-07 | OM07-ID |
| Water | Blue  | 145.7 kHz | OM-08 | OM08-ID |
| Power | Red  | 169.8 kHz | OM-09 | OM09-ID |



中国大陆代理商

深圳市谱兆通讯设备有限公司

Tel:+86-755-8665-5448;+86-755-8665-5579; Email:info@pztest.com Website:www.pztest.com