



JETAIR 100270

JETTING FTTX BLOWING COMPRESSOR

The compact engine-driven (petrol) compressor makes FTTX installations easier and more flexible in the field. With a free air delivery of approximately 100 l/min at 8 bar, and with an integrated aftercooler and humidity filter, this compressor supports your fiber blowing work perfectly and allows you to operate completely independent of external power supply.

JetAir 100270 is designed for fiber blowing in micro-ducts with internal diameters up to 4 mm. Its lightweight yet robust construction makes transport and setup quick and easy. Combined with Jetting's Trigg AIR or the VO fiber blowing machine, it provides a reliable and efficient solution for smaller installation projects.

The JetAir 100270 is supplied with a 10 m air hose.



JETAIR 100270

- Max pressure: 10 bar
- Free Air Delivery (FAD): approx. 100 l/min @ 8 bar
- Intake air flow: 0.270 m³/min
- Subaru Robin engine, 3 HP (manual start)
- Built-in aftercooler and water separator
- Oil-free air delivery
- Outlet: 1 × 3/8" CEJN connector
- 4-stroke engine
- Vibration dampening rubber feet
- Suitable for micro-duct jetting up to Ø 4 mm
- Fuel type: 95 octane
- Fuel tank: 3.5 liters
- Noise level: 80 dB(A) LpA / 94 dB(A) LwA
- Dimensions: L 510 × H 420 × W 306 mm
- Weight: 24.5 kg
- Article number: 660506

